

Ventia – EastLink Tunnel

Ventilation Stack Air Quality Monitoring Validated Data Report 01 January 2024 to 31 March 2024

Ref: DR.2024Q1.ETL Issue Date: 24 April 2024 Report prepared by: Tim Allfrey

NATA Accredited Laboratory Number 19660

Accredited for compliance with ISO/IEC17025 – Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian / national standards.



Norditech Pty Ltd Unit 2/87 Station Road Seven Hills NSW 2147

1300 572 822

info@norditech.com.au norditech.com.au



Document Control

Revision	Date	Details	Prepared By	Approved By
0	24/04/2024		ТА	BN

Prepared by

Alugy

Tim Allfrey 24 April 2024

Approved by



Bruno Nourdine 24 April 2024

Distribution

Format	Recipient	Details
PDF	George Vasiliadis	GVasiliadis@connecteast.com.au
PDF	Nick Huntington	NHuntington@connecteast.com.au





Table of Contents

1		
	1.1 Compliance to limits	5
	1.2 Summary of Results	7
2	Compliance Limits	9
	2.1 Standards Compliance	
3		
4		
	4.1 Methodology	
	4.2 Ventilation Stacks	
	4.3 Data Collection	
	4.4 Data Validation	
	4.5 Reporting and Calculations	
	4.5.1 Data Availability	
	4.5.2 Unit Conversions	
5		
0	5.1 Units and Uncertainties	
	5.2 Last Calibrations and Maintenance records	
	5.3 Automatic Instrument Calibration Checks	
6		
U	6.1 January 2024	
	6.1.1 Data Availability	
	6.1.2 Exceedances	
	6.1.3 Tabulated Results	
	6.1.3.1 Statistical Summary of 1-hour Mass Rate Data Western and Eastern Ventilation Stacks	
	6.1.4 Graphical Representations	
	6.1.4.1 January 2024 - Monthly 1-hour mass rate NO ₂	
	6.1.4.2 January 2024 - Monthly 1-hour mass rate NO	
	6.1.4.3 January 2024 - Monthly 1-hour mass rate CO	
	6.1.4.4 January 2024 - Monthly 1-hour mass rate PM _{2.5}	
	6.1.4.5 January 2024 - Monthly 1-hour mass rate PM ₁₀	
	6.1.4.6 January 2024 - Monthly 1-hour average stack velocity	
	6.1.4.7 January 2024 - Monthly 1-hour average stack temperature	
	6.1.5 Data Validation Table	
	6.1.5.1 January 2024 - Western Ventilation Stack	
	6.1.5.2 January 2024 - Eastern Ventilation Stack6.2 February 2024	
	6.2.1 Data Availability	
	•	
	6.2.3 Tabulated Results 6.2.3.1 Statistical Summary of 1-hour Mass Rate Data Western and Eastern Ventilation Stacks	
	6.2.3.1 Statistical Summary of 1-hour Mass Rate Data Western and Eastern Ventilation Stacks 6.2.4 Graphical Representations	
	6.2.4.1 February 2024 - Monthly 1-hour mass rate NO ₂	
	6.2.4.2 February 2024 - Monthly 1-hour mass rate NO	
	6.2.4.3 February 2024 - Monthly 1-hour mass rate CO	
	6.2.4.4 February 2024 - Monthly 1-hour mass rate PM _{2.5}	
	6.2.4.5 February 2024 - Monthly 1-hour mass rate PM ₁₀	
	6.2.4.6 February 2024 - Monthly 1-hour average stack velocity	
	6.2.4.7 February 2024 - Monthly 1-hour average stack temperature	
	6.2.5 Data Validation Table	
	6.2.5.1 February 2024 - Western Ventilation Stack	
	6.2.5.2 February 2024 - Eastern Ventilation Stack	
	6.3 March 2024	44





6.3.1 Data Availability	44
6.3.2 Exceedances	
6.3.3 Tabulated Results	
6.3.3.1 Statistical Summary of 1-hour mass rate data Western and Eastern Ventilation Stacks	-
6.3.4 Graphical Representations	
6.3.4.1 March 2024 - Monthly 1-hour mass rate NO ₂	
6.3.4.2 March 2024 - Monthly 1-hour mass rate NO ₂	
6.3.4.3 March 2024 - Monthly 1-hour mass rate CO	
6.3.4.4 March 2024 - Monthly 1-hour mass rate PM _{2.5}	
6.3.4.5 March 2024 - Monthly 1-hour mass rate PM ₁₀	
6.3.4.6 March 2024 - Monthly 1-hour average stack velocity	
6.3.4.7 March 2024 - Monthly 1-hour average stack temperature	
6.3.5 Data Validation Table	
6.3.5.1 March 2024 - Western Ventilation Stack	
6.3.5.2 March 2024 - Western Ventilation Stack	
6.4 Data Availability Year to Date	
6.5 Annual Performance Statement Bubble Limits	
7 Report Summary	
Appendix 1	
Glossary	
Data Validation Explanations	59

Figures

Figure 1: EastLink Tunnel ventilation stack locations	12
Figure 2: January 2024 Monthly 1-hour mass rate NO2	23
Figure 3: January 2024 Monthly 1-hour mass rate NO	
Figure 4: January 2024 Monthly 1-hour mass rate CO	25
Figure 5: January 2024 Monthly 1-hour mass rate PM _{2.5}	26
Figure 6: January 2024 Monthly 1-hour mass rate PM ₁₀	27
Figure 7: January 2024 Monthly 1-hour average stack velocity	28
Figure 8: January 2024 Monthly 1-hour average stack temperature	29
Figure 9: February 2024 Monthly 1-hour mass rate NO2	35
Figure 10: February 2024 Monthly 1-hour mass rate NO	36
Figure 11: February 2024 Monthly 1-hour mass rate CO	37
Figure 12: February 2024 Monthly 1-hour mass rate PM _{2.5}	38
Figure 13: February 2024 Monthly 1-hour mass rate PM ₁₀	39
Figure 14: February 2024 Monthly 1-hour average stack velocity	40
Figure 15: February 2024 Monthly 1-hour average stack temperature	41
Figure 16: March 2024 Monthly 1-hour mass rate NO ₂	47
Figure 17: March 2024 Monthly 1-hour mass rate NO	
Figure 18: March 2024 Monthly 1-hour mass rate CO	49
Figure 19: March 2024 Monthly 1-hour mass rate PM _{2.5}	50
Figure 20: March 2024 Monthly 1-hour mass rate PM ₁₀	51
Figure 21: March 2024 Monthly 1-hour average stack velocity	
Figure 22: March 2024 Monthly 1-hour average stack temperature	53
Figure 23: Annual Performance Statement stack emission rates	57







	_
Table 1: January 2024 Exceedances of EPA Limits	
Table 2: February 2024 Exceedances of EPA Limits	
Table 3: March 2024 Exceedances of EPA Limits	
Table 4: January 2024 Summary of results. Table 5: Tabuary 2024 Summary of results.	
Table 5: February 2024 Summary of results Table 0: Marsh 2024 Summary of results	
Table 6: March 2024 Summary of results	
Table 7: EPA Compliance Limits	
Table 8: Measurement methods and instrumentation	
Table 9: EastLink Tunnel ventilation stack GPS Coordinates	
Table 10: Measurement units and uncertainties Table 14: January 2004 Instrument as liberation dates	
Table 11: January 2024 Instrument calibration dates	
Table 12: February 2024 Instrument calibration dates	
Table 13: March 2024 Instrument calibration dates Table 14: Nightheorem	
Table 14: Nightly span, zero and CO reference times. Table 45: January 2004 were the image of the service billing of the service billing.	
Table 15: January 2024 ventilation stack data availability	
Table 16: January 2024 Exceedances of EPA Goals	
Table 17: January 2024 Summary of 1-hour mass rate pollutant data	
Table 18: January 2024 Western Ventilation Stack data validation Table 18: January 2024 Western Ventilation Stack data validation	
Table 19: January 2024 Eastern Ventilation Stack data validation	
Table 20: February 2024 ventilation stack data availability	
Table 21: February 2024 Exceedances of EPA Goals	
Table 22: February 2024 Summary of 1-hour mass rate pollutant data	
Table 23: February 2024 Western Ventilation Stack data validation	
Table 24: February 2024 Eastern Ventilation Stack data validation	
Table 25: March 2024 ventilation stack data availability	
Table 26: March 2024 Exceedances of EPA Goals	-
Table 27: March 2024 Summary of 1-hour mass rate pollutant data	
Table 28: March 2024 Western Ventilation Stack data validation	
Table 29: March 2024 Eastern Ventilation Stack data validation	
Table 30: EastLink Ventilation Stack year to date data availability	
Table 31: Annual Performance Statement stack emission rates	57





1 Executive Summary

EastLink is a 39 km motorway running between Nunawading and Frankston, linking the Eastern, Monash Frankston and Peninsula Link freeways. Two 1.6 km tunnels pass under the Mullum Mullum Valley, with a ventilation stack at the end of each tunnel as an exit point for tunnel ventilation.

Two ventilation stacks provide ventilation for the tunnel, one at the western end of the tunnel at Discharge Point 1 (DP1), and one at the eastern end of the tunnel at Discharge Point 2 (DP2).

This report presents the monthly validated stack data for January 2024 to March 2024 to Ventia Pty Ltd for the EastLink Tunnel.

1.1 Compliance to limits

The Environment Protection Authority (Victoria) designates limits to which pollutant mass rates being discharged from the ventilation stacks must meet. (Environmental Licence No. 2043).

Instances of the ventilation stack pollutants exceeding the EPA Limits goals during the reporting period are presented in Table 1, Table 2 and Table 3 and below. Maximum mass rates are provided for comparison to the limits.

EastLink Ventiliation Stack Air Quality Limit Exceedances January 2024											
Location	Parameter	Time Period	Licence Limit	Units	Maximum Mass Rate	Number of exceedances	Value of exceedance	Date and Time of exceedance			
	NO ₂	1-hour	3.98	kg/h	0.27	-	-	-			
Western Ventilation Stack	со	1-hour	112	kg/h	5.07	-	-	-			
(Discharge Point 1)	PM _{2.5}	1-hour	2.4	kg/h	0.14	-	-	-			
	PM ₁₀	1-hour	2.6	kg/h	0.39	-	-	-			
F (NO ₂	1-hour	3.98	kg/h	0.63	-	-	-			
Eastern Ventilation	со	1-hour	112	kg/h	6.71	-	-	-			
Stack (Discharge Point 2)	PM _{2.5}	1-hour	2.4	kg/h	0.19	-	-	-			
	PM ₁₀	1-hour	2.6	kg/h	0.48	-	-	-			

There were nil exceedances of the prescribed limits during the reporting period.

Table 1: January 2024 Exceedances of EPA Limits





EastLink Ventiliation Stack Air Quality Limit Exceedances February 2024											
Location	Parameter	Time Period	Licence Limit	Units	Maximum Mass Rate	Number of exceedances	Value of exceedance	Date and Time of exceedance			
	NO ₂	1-hour	3.98	kg/h	0.60	-	-	-			
Western Ventilation Stack	со	1-hour	112	kg/h	6.55	-	-	-			
(Discharge Point 1)	PM _{2.5}	1-hour	2.4	kg/h	0.17	-	-	-			
T On (CT)	PM ₁₀	1-hour	2.6	kg/h	0.42	-	-	-			
Frater	NO ₂	1-hour	3.98	kg/h	0.74	-	-	-			
Eastern Ventilation Stack	со	1-hour	112	kg/h	8.41	-	-	-			
(Discharge Point 2)	PM _{2.5}	1-hour	2.4	kg/h	0.17	-	-	-			
Point 2)	PM ₁₀	1-hour	2.6	kg/h	0.83	-	-	-			

Table 2: February 2024 Exceedances of EPA Limits

EastLink Ventiliation Stack Air Quality Limit Exceedances March 2024											
Location	Parameter	Time Period	Licence Limit	Units	Maximum Mass Rate	Number of exceedances	Value of exceedance	Date and Time of exceedance			
	NO ₂	1-hour	3.98	kg/h	0.53	-	-	-			
Western Ventilation	со	1-hour	112	kg/h	6.33	-	-	-			
Stack (Discharge Point 1)	PM _{2.5}	1-hour	2.4	kg/h	0.23	-	-	-			
1 0/1/2 1)	PM ₁₀	1-hour	2.6	kg/h	0.36	-	-	-			
Fraters	NO ₂	1-hour	3.98	kg/h	0.69	-	-	-			
Eastern Ventilation	со	1-hour	112	kg/h	8.16	-	-	-			
Stack (Discharge Point 2)	PM _{2.5}	1-hour	2.4	kg/h	0.16	-	-	-			
	PM ₁₀	1-hour	2.6	kg/h	0.42	-	-	-			

Table 3: March 2024 Exceedances of EPA Limits





1.2 Summary of Results

Summaries of the ventilation stack pollutants for the reporting period are presented in Table 4, Table 5 and Table 6 below. Maximum mass rates are provided for comparison to the limits.

EastLink Ventilation Stack Summary January 2024										
Location	Parameter	1hr Average Maximum	1 hr Average Minimum	Monthly Average	Monthly Total	Number of Exceedances	Data Availability (%)			
	NO (kg/h)	2.31	-0.01	0.40	281.62	N/A	95.6%			
	NO ₂ (kg/h)	0.27	0.00	0.06	41.18	0	95.6%			
Western Ventilation Stack	CO (kg/h)	5.07	-0.04	1.45	1029.53	0	95.6%			
	PM _{2.5} (kg/h)	0.1	0.0	0.0	16.0	0	85.8%			
	PM ₁₀ (kg/h)	0.4	0.0	0.0	30.4	0	98.9%			
	NO (kg/h)	2.81	-0.23	0.53	379.02	N/A	95.6%			
	NO ₂ (kg/h)	0.63	0.00	0.11	78.66	0	95.6%			
Eastern Ventilation Stack	CO (kg/h)	6.71	-0.04	1.43	1018.37	0	95.6%			
	PM _{2.5} (kg/h)	0.2	0.0	0.0	21.8	0	98.4%			
	PM ₁₀ (kg/h)	0.5	0.0	0.1	38.7	0	87.2%			

Table 4: January 2024 Summary of results





EastLink Ventilation Stack Summary February 2024										
Location	Parameter	1hr Average Maximum	1 hr Average Minimum	Monthly Average	Monthly Total	Number of Exceedances	Data Availability (%)			
	NO (kg/h)	2.54	-0.01	0.53	322.15	N/A	87.9%			
	NO ₂ (kg/h)	0.60	-0.01	0.08	48.02	0	87.9%			
Western Ventilation Stack	CO (kg/h)	6.55	-0.06	1.78	1168.21	0	94.5%			
	PM _{2.5} (kg/h)	0.2	0.0	0.0	19.2	0	86.8%			
	PM ₁₀ (kg/h)	0.4	0.0	0.1	42.1	0	98.6%			
	NO (kg/h)	3.25	-0.18	0.76	504.47	N/A	95.5%			
	NO ₂ (kg/h)	0.74	0.00	0.15	100.55	0	95.5%			
Eastern Ventilation Stack	CO (kg/h)	8.41	-0.02	1.79	1193.64	0	94.5%			
	PM _{2.5} (kg/h)	0.2	0.0	0.0	26.7	0	86.8%			
	PM ₁₀ (kg/h)	0.8	0.0	0.1	60.7	0	98.6%			

Table 5: February 2024 Summary of results

EastLink Ventilation Stack Summary March 2024										
Location	Parameter	1hr Average Maximum	1 hr Average Minimum	Monthly Average	Monthly Total	Number of Exceedances	Data Availability (%)			
	NO (kg/h)	2.88	-0.01	0.55	388.28	N/A	<mark>95.0%</mark>			
	NO ₂ (kg/h)	0.53	0.00	0.09	61.53	0	95.0%			
Western Ventilation Stack	CO (kg/h)	6.33	-0.05	1.76	1245.19	0	95.0%			
	PM _{2.5} (kg/h)	0.2	0.0	0.0	22.1	0	94.8%			
	PM ₁₀ (kg/h)	0.4	0.0	0.0	36.7	0	99.2%			
	NO (kg/h)	3.07	-0.21	0.68	479.78	N/A	95.4%			
	NO ₂ (kg/h)	0.69	0.00	0.13	94.71	0	95.4%			
Eastern Ventilation Stack	CO (kg/h)	8.16	-0.02	1.72	1223.84	0	95.4%			
	PM _{2.5} (kg/h)	0.2	0.0	0.0	25.2	0	99.3%			
	PM ₁₀ (kg/h)	0.4	0.0	0.1	57.5	0	99.2%			

Table 6: March 2024 Summary of results





2 Compliance Limits

Air quality limits are provided in Condition LI_DA1.13 of the Environment Protection Authority (Victoria) Licence No 2043 for the EastLink Tunnel. The air quality limits for 1-hour mass rates are shown in Table 7 below.

EastLink Ventiliation Stack Air Quality Limits									
Location	Parameter	r Time Period License L		Units	Applicable Licence				
	NO ₂	1-hour	3.98	kg/h					
Western Ventilation Stack	СО	1-hour	112	kg/h	EPA Vic				
(Discharge Point 1)	PM _{2.5}	1-hour	2.4	kg/h	Licence No 2043				
	PM ₁₀	1-hour	2.6	kg/h					
	NO ₂		3.98	kg/h					
Eastern Ventilation Stack	СО	1-hour	112	kg/h	EPA Vic				
(Discharge Point 2)	PlVb - 1 1-hour		2.4	kg/h	Licence No 2043				
	PM ₁₀	1-hour	2.6	kg/h					

Table 7: EPA Compliance Limits

The procedure for reporting particulate matter results from the TEOMs and assessment of licence compliance is detailed in the EastLink Particulate Matter Protocol (PMP) dated 17/06/2013. The PMP requires validated uncorrected TEOM one hour clock average data to be compared to the following TEOM mass rate compliance limits for both DP1 and DP2.

- PM_{2.5}: 2.0 kg/h
- PM₁₀: 2.0 kg/h

2.1 Standards Compliance

Norditech's NATA Accreditation does not cover the following parameters monitored at the EastLink Tunnel ventilation stack air quality monitoring stations.

- Measurement of Stack Flow.
- AS/NZS 3580.9.8 refers specifically to the monitoring of PM₁₀.





3 Introduction

Norditech were contracted by Ventia Pty Ltd in August 2021 to provide continuous stack air quality monitoring and reporting services for the EastLink Tunnel. Ventia Pty Ltd are responsible for the operation and maintenance of the motorway.

Norditech is a NATA accredited organisation (Accreditation Number 19660).

Addresses of relevant parties:

Norditech Pty Ltd 2/87 Station Rd Seven Hills NSW 2147 Ventia Pty Ltd 2 Hillcrest Avenue Ringwood VIC 3134

This report presents the validated Western and Eastern ventilation stack data for January 2024 to March 2024.

- Describes air quality measurements.
- Reports any readings above the relevant EPA Limits.
- Compares monitoring results.
- Has been quality assured.





4 Explanation of Monitoring

4.1 Methodology

In the tunnel air is discharged via two ventilation stacks – one located at the Western end of the tunnel (DP1), and one located at the Eastern end (DP2). For each stack, monitoring as per the requirements of EPA Licence 2043 is undertaken.

Gaseous parameters are sampled by an extractive sampling system. Oxides of nitrogen are measured using chemiluminescence. Carbon monoxide is measured using non-dispersive infra-red absorption.

Particulates PM₁₀ and PM_{2.5} are measured using tapered element oscillating microbalances.

Stack gas velocity is measured using an optical flow sensor.

Monthly routine maintenance is undertaken by Norditech. Maintenance is performed as per the relevant Australian Standard or in house method. Maintenance cycles generally involve 1, 3, 6 and 12 monthly scheduled items.

The following instrumentation and methods are used in data collection:

EastLink Ventilation Stack Measurement Methods							
Parameter	Method	Instrument					
со	In house method TP.003	Thermo Scientific 48i					
NO, NO_2, NO_x	In house method TP.001 Thermo Scientific 42i						
	AS/NZS 3580.9.8						
PM ₁₀	In house method TP.005	Rupprecht & Patashnick TEOM					
	AS 4323.1						
DM	In house method TP.026						
PM _{2.5}	AS 4323.1	Rupprecht & Patashnick TEOM					
Temperature	In house method TP.012	PT100					
Stack Velocity	USEAP (CFR 40) Part 75	OSI OFS2000					

Table 8: Measurement methods and instrumentation





4.2 Ventilation Stacks

The locations of the EastLink Tunnel Western and Eastern ventilation stacks are detailed in Table 9 and Figure 1 below.

EastLink Ventilation Stack Locations						
Discharge Point Site Name		GPS Coordinates				
1	Western Ventilation Stack	-37.801229°, 145.196092°				
2	Eastern Ventilation Stack	-37.808885°, 145.212012°				

Table 9: EastLink Tunnel ventilation stack GPS Coordinates




Figure 1: EastLink Tunnel ventilation stack locations

:





4.3 Data Collection

At each Air Quality Monitoring Station, data is logged to an EnviDAS data logger at 1 minute average intervals. Each 1-minute average is calculated from data sampled at 10 second intervals.

Data is transferred automatically to Norditech's data collection software via a TCP/IP link over 4G cellular network, at a frequency of not less than 1-hour. Two datasets are maintained by Norditech, one for data validation and reporting purposes, and a non-validated data set for reference purposes.

4.4 Data Validation

Data validation is performed as per Norditech's data validation procedure TP.022. The data validation process identifies any data that is deemed not to be valid. This data is flagged as invalid in the database and is removed from the reported data.

Data may be deemed invalid for several reasons, including but not limited to:

- Instrument fault.
- Instrument calibration out of tolerance.
- Maintenance activities.

For further details and explanations of reasons for invalidating data, please refer to Appendix 1 – Data Validation Explanations.

Initial visual inspection of data is performed by inspection of graphs to identify any anomalies in the data set.

Site visit logs and maintenance and calibration certificates are cross referenced to the data set and any data affected by maintenance activities are flagged.

Instrument drift and calibration tolerances are checked, and data flagged in the database as necessary as per NATA compliance requirements.





4.5 Reporting and Calculations

All calculations and averages are calculated from 1 minute average base data and are reported as 'end time' when the averaging periods of eight hours or less. IE the average data for 01:00 is the data from 00:00 through to 01:00. One-hour averages are calculated based on a clock hour. One day averages are calculated based on calendar days. All averages are based on a minimum of 75% valid readings within the averaging period.

All data is reported at Australian Eastern Standard Time.

Validated data for Quarter 1 Month 1 is presented in the Excel workbook named "202401 EastLink Q1M1 Validated data.xlsx"

The workbooks each consist of the following sheets:

Sheet 1: Cover Sheet 2: M1 Data kg1h – Hourly data in kg/h Sheet 3: M1 Data g5m – 5-minute data in grams/5m Sheet 4: M1 Data mgm3 1h – 1-hour data in mg/m³ Sheet 5: M1 Data mgm3 5m – 5-minute data in mg/m³ Sheet 6: Eastern Validation Data Sheet 7: Western Validation Data

Validated data for Quarter 1 Month 2 is presented in the Excel workbook named "202402 EastLink Q4M2 Validated data.xlsx"

The workbooks each consist of the following sheets:

Sheet 1: Cover Sheet 2: M2 Data kg1h – Hourly data in kg/h Sheet 3: M2 Data g5m – 5-minute data in grams/5m Sheet 4: M2 Data mgm3 1h – 1-hour data in mg/m³ Sheet 5: M2 Data mgm3 5m – 5-minute data in mg/m³ Sheet 6: Eastern Validation Data Sheet 7: Western Validation Data

Validated data for Quarter 1 Month 3 is presented in the Excel workbook named "202403 EastLink Q4M3 Validated data.xlsx"

The workbook consists of the following sheets:

Sheet 1: Cover Sheet 2: M3 Data kg1h – Hourly data in kg/h Sheet 3: M3 Data g5m – 5-minute data in grams/5m Sheet 4: M3 Data mgm3 1h – 1-hour data in mg/m³ Sheet 5: M3 Data mgm3 5m – 5-minute data in mg/m³ Sheet 6: Eastern Validation Data Sheet 7: Western Validation Data





4.5.1 Data Availability

Data availability refers to the amount of available 1-hour data for the reporting period. Data availability is calculated using the following formula:

 $Data availability \% = \frac{sum of available data points}{sum of possible data points} * 100$

Where:

- Sum of available data points is the number of validated 1-hour average data points for the reporting period.
- Sum of possible data points is the number of theoretically available 1-hour data points for the reporting period.

4.5.2 Unit Conversions

Stack velocity readings are converted to flow rate using the following stack areas:

- Western Stack area 35 m²
- Eastern Stack area 35 m²

Pollutant and flow data are reported at actual conditions.





5 Calibrations and Maintenance

5.1 Units and Uncertainties

EastLink Ventilation Stack Instrument Units and Uncertainties								
Parameter	Units	Resolution	Uncertainty	Measurement Range				
со	mg/m ³	0.01	± 8.2% of reading at 62.5mg/m ³ (k=1.96)	0 to 200				
NO	mg/m ³	0.01	± 8.1% of reading for range 25.7 – 32.8mg/m ³ (k=1.96)	0 to 150				
NO ₂	mg/m ³	0.01	± 8.5% of reading at 25.7mg/m ³ (k=1.96)	0 to 150				
NO _x	mg/m ³	0.01	± 8.1% of reading for range 25.7 – 32.8mg/m ³ (k=1.96)	0 to 150				
PM ₁₀	µg/m³	0.1	±5.0 μg/m ³ or 3.6% of reading, whichever is the greater. K factor of 1.96	0 to 5000				
PM _{2.5}	µg/m³	0.1	±5.0 μg/m ³ or 3.6% of reading, whichever is the greater. K factor of 1.96	0 to 5000				
Temperature	°C	0.1	±2.0 °C1	-25 to 105				
Stack Velocity	m/s	1	±0.1 m/s ¹	-40 to +40				

¹ Manufacturer's stated accuracy

Table 10: Measurement units and uncertainties





5.2 Last Calibrations and Maintenance records

Instrumentation maintenance and last calibration dates are provided in Table 11, Table 12 and Table 13 below:

EastLink Ventilation Stack Maintenance and Calibrations January 2024								
Location	Parameter	Date of last scheduled maintenance	Maintenance type	Date of last calibration				
	CO	17/01/2024	1 Monthly	17/01/2024				
Western	NO, NO ₂	17/01/2024	1 Monthly	17/01/2024				
Ventilation Stack	PM ₁₀	14/12/2023	6 Monthly	14/12/2023				
(Discharge	PM _{2.5}	14/12/2023	6 Monthly	14/12/2023				
Point 1)	Stack Velocity	31/08/2022	12 Monthly	31/08/2022				
	Stack Temperature	14/12/2023	6 Monthly	14/12/2023				
	CO	17/01/2024	1 Monthly	17/01/2024				
Eastern	NO, NO ₂	17/01/2024	1 Monthly	17/01/2024				
Ventilation	PM ₁₀	15/12/2023	6 Monthly	15/12/2023				
Stack (Discharge	PM _{2.5}	15/12/2023	6 Monthly	15/12/2023				
Point 2)	Stack Velocity	31/08/2022	12 Monthly	31/08/2022				
,	Stack Temperature	15/12/2023	6 Monthly	15/12/2023				

Table 11: January 2024 Instrument calibration dates

EastLink Ventilation Stack Maintenance and Calibrations February 2024								
Location	Parameter	Date of last scheduled maintenance	Maintenance type	Date of last calibration				
	CO	13/02/2024	1 Monthly	13/02/2024				
Western	NO, NO ₂	13/02/2024	1 Monthly	13/02/2024				
Ventilation Stack	PM ₁₀	14/12/2023	6 Monthly	14/12/2023				
(Discharge	PM _{2.5}	14/12/2023	6 Monthly	14/12/2023				
Point 1)	Stack Velocity	31/08/2022	12 Monthly	31/08/2022				
	Stack Temperature	14/12/2023	6 Monthly	14/12/2023				
	CO	18/02/2024	1 Monthly	18/02/2024				
Eastern	NO, NO ₂	18/02/2024	1 Monthly	18/02/2024				
Ventilation	PM ₁₀	15/12/2023	6 Monthly	15/12/2023				
Stack (Discharge	PM _{2.5}	15/12/2023	6 Monthly	15/12/2023				
Point 2)	Stack Velocity	31/08/2022	12 Monthly	31/08/2022				
	Stack Temperature	15/12/2023	6 Monthly	15/12/2023				

Table 12: February 2024 Instrument calibration dates





EastLink Ventilation Stack Maintenance and Calibrations March 2024								
Location	Parameter	Date of last scheduled maintenance	Maintenance type	Date of last calibration				
	CO	28/03/2024	3 Monthly	28/03/2024				
Western	NO, NO ₂	28/03/2024	3 Monthly	28/03/2024				
Ventilation Stack	PM ₁₀	28/03/2024	3 Monthly	14/12/2023				
(Discharge	PM _{2.5}	28/03/2024	3 Monthly	14/12/2023				
Point 1)	Stack Velocity	31/08/2022	12 Monthly	31/08/2022				
· · · · · · · · · · · · · · · · · · ·	Stack Temperature	14/12/2023	6 Monthly	14/12/2023				
	CO	28/03/2024	3 Monthly	28/03/2024				
Eastern	NO, NO ₂	28/03/2024	3 Monthly	28/03/2024				
Ventilation	PM ₁₀	28/03/2024	3 Monthly	15/12/2023				
Stack (Discharge	PM _{2.5}	15/12/2023	6 Monthly	15/12/2023				
Point 2)	Stack Velocity	31/08/2022	12 Monthly	31/08/2022				
	Stack Temperature	15/12/2023	6 Monthly	15/12/2023				

Table 13: March 2024 Instrument calibration dates





5.3 Automatic Instrument Calibration Checks

Table 14 below identifies the times at which the daily gaseous parameter automatic span and zero checks are performed.

This data is removed from the dataset, however, are not included in the data validation tables of data.

Nightly span and zero times for NO, NO_2 and CO						
Location	Parameter	Span / Zero cycle time				
Western	CO	00:00 - 00:34				
western	NO, NO_2	01:00 - 01:44				
Eastern	CO	01:34 - 02:13				
Eastern	NO, NO_2	01:34 - 02:13				

Table 14: Nightly span, zero and CO reference times.





6 Results

6.1 January 2024

6.1.1 Data Availability

Data availability for the in the ventilation stack parameters are provided in Table 15 below. For further information on data availability please refer to section 6.1.5.

EastLink Ventilation Stack Data Availability January 2024										
Station		NO	NO ₂	со	PM _{2.5}	PM ₁₀	Stack Velocity	Stack Temp.		
	Data Availability	95.6%	95.6%	95.6%	85.8%	98.9%	100.0%	100.0%		
Western	Collected Periods	711.0	711.0	711.0	638.0	736.0	744.0	744.0		
	Available Periods	744.0	744.0	744.0	744.0	744.0	744.0	744.0		
	Data Availability	95.6%	95.6%	95.6%	98.4%	87.2%	100.0%	90.1%		
Eastern	Collected Periods	711.0	711.0	711.0	732.0	649.0	744.0	670.0		
	Available Periods	744.0	744.0	744.0	744.0	744.0	744.0	744.0		

Table 15: January 2024 ventilation stack data availability





6.1.2 Exceedances

Instances of the ventilation stack pollutants exceeding the EPA Limits goals during the reporting period are presented in Table 16 below. Maximum mass rates are provided for comparison to the limits.

EastLink Ventiliation Stack Air Quality Limit Exceedances January 2024									
Location	Parameter	Time Period	Licence Limit	Units	Maximum Mass Rate	Number of exceedances	Value of exceedance	Date and Time of exceedance	
Mantana	NO ₂	1-hour	3.98	kg/h	0.27	-	-	-	
Western Ventilation Stack	со	1-hour	112	kg/h	5.07	-	-	-	
(Discharge Point 1)	PM _{2.5}	1-hour	2.4	kg/h	0.14	-	-	-	
T Offic Ty	PM ₁₀	1-hour	2.6	kg/h	0.39	-	-	-	
	NO ₂	1-hour	3.98	kg/h	0.63	-	-	-	
Eastern Ventilation	со	1-hour	112	kg/h	6.71	-	-	-	
Stack (Discharge Point 2)	PM _{2.5}	1-hour	2.4	kg/h	0.19	-	-	-	
Point 2)	PM ₁₀	1-hour	2.6	kg/h	0.48	-	-	-	

There were nil exceedances of the prescribed limits during the reporting period.

Table 16: January 2024 Exceedances of EPA Goals





6.1.3 Tabulated Results

6.1.3.1 Statistical Summary of 1-hour Mass Rate Data Western and Eastern Ventilation Stacks

Table 17 presents 1-hour mass rate statistical data for the Western and Eastern ventilation stacks.

1-hour mass rates are calculated from 1 minute average data.

EastLink Ventilation Stack Summary January 2024									
Location	Parameter	Maximum	99 th Percentile	98 th Percentile	95 th Percentile	90 th Percentile	75 th Percentile	50 th Percentile	
	NO (kg/h)	2.31	1.98	1.85	1.21	0.88	0.64	0.35	
	NO ₂ (kg/h)	0.27	0.22	0.20	0.15	0.13	0.09	0.06	
Western Ventilation Stack	CO (kg/h)	5.07	4.54	4.21	3.58	2.97	2.36	1.78	
	PM _{2.5} (kg/h)	0.1	0.1	0.1	0.1	0.1	0.0	0.0	
	PM ₁₀ (kg/h)	0.4	0.2	0.2	0.1	0.1	0.1	0.0	
	NO (kg/h)	2.81	2.35	2.12	1.69	1.39	0.80	0.43	
	NO ₂ (kg/h)	0.63	0.53	0.46	0.36	0.26	0.17	0.10	
Eastern Ventilation Stack	CO (kg/h)	6.71	5.32	4.76	3.82	3.14	2.39	1.60	
	PM _{2.5} (kg/h)	0.2	0.1	0.1	0.1	0.1	0.0	0.0	
	PM ₁₀ (kg/h)	0.5	0.3	0.3	0.2	0.1	0.1	0.0	

Table 17: January 2024 Summary of 1-hour mass rate pollutant data





6.1.4 Graphical Representations

The following charts present 1-hour mass rate data for NO, NO₂, CO, PM_{2.5}, PM₁₀ and Stack Velocity for the Western and Eastern ventilation stacks.

1-hour mass rates are calculated from 1 minute average data.

6.1.4.1 January 2024 - Monthly 1-hour mass rate NO2




Figure 2: January 2024 Monthly 1-hour mass rate NO2





6.1.4.2 January 2024 - Monthly 1-hour mass rate NO




Figure 3: January 2024 Monthly 1-hour mass rate NO





6.1.4.3 January 2024 - Monthly 1-hour mass rate CO




Figure 4: January 2024 Monthly 1-hour mass rate CO





6.1.4.4 January 2024 - Monthly 1-hour mass rate PM_{2.5}




Figure 5: January 2024 Monthly 1-hour mass rate PM_{2.5}





6.1.4.5 January 2024 - Monthly 1-hour mass rate PM₁₀




Figure 6: January 2024 Monthly 1-hour mass rate PM10





6.1.4.6 January 2024 - Monthly 1-hour average stack velocity




Figure 7: January 2024 Monthly 1-hour average stack velocity





6.1.4.7 January 2024 - Monthly 1-hour average stack temperature




Figure 8: January 2024 Monthly 1-hour average stack temperature





6.1.5 Data Validation Table

Data validation details for the ventilation stack parameters are provided in the Table 18 and Table 19 below.

6.1.5.1 January 2024 - Western Ventilation Stack

	Eastlink Tur	nnel Western Ven	tilation Stack Data Validation Ja	nuary 20)24	
Start Date	End Date	Parameters	Reason	Hours affected	User Name	Change Date
1/01/2024 00:00	17/01/2024 06:38	со	Offset applied to data: Offset A: -0.3 Offset B: -0.3	N/A	ТА	19/04/2024
1/01/2024 00:00	17/01/2024 06:38	NO	Multiplier applied to data: Multiplier A: 1.0 Multiplier B: 0.944711	N/A	ТА	19/04/2024
1/01/2024 00:00	17/01/2024 06:38	NO _x	Multiplier applied to data: Multiplier A: 1.0 Multiplier B: 0.925845	N/A	ТА	19/04/2024
2/01/2024 19:06	31/01/2024 02:33	PM _{2.5} , PM ₁₀	Intermittent unrealistic data - negative	N/A	ТА	19/04/2024
13/01/2024 16:13	13/01/2024 16:31	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	0.3	ТА	19/04/2024
13/01/2024 17:36	13/01/2024 18:21	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	0.8	ТА	19/04/2024
13/01/2024 19:14	13/01/2024 19:28	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	0.2	ТА	19/04/2024
14/01/2024 03:07	14/01/2024 13:25	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	10.3	ТА	19/04/2024
14/01/2024 16:50	14/01/2024 18:58	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	2.1	ТА	19/04/2024
17/01/2024 04:21	17/01/2024 06:19	PM _{2.5}	Unrealistic data - PM _{2.5} > PM ₁₀	2.0	ТА	19/04/2024
17/01/2024 06:38	17/01/2024 07:38	CO, NO, NO ₂ , NOx, PM _{2.5} , PM ₁₀	Maintenance	1.0	ТА	19/04/2024
17/01/2024 07:39	13/02/2024 08:17	со	Offset applied to data: Offset A: 0.0 Offset B: -0.3	N/A	TA	19/04/2024
17/01/2024 16:20	18/01/2024 07:58	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	15.6	ТА	19/04/2024
19/01/2024 10:07	21/01/2024 01:44	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	39.6	ТА	19/04/2024
24/01/2024 05:14	24/01/2024 06:16	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	1.0	ТА	19/04/2024
27/01/2024 12:55	28/01/2024 08:06	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	19.2	ТА	19/04/2024
28/01/2024 08:07	28/01/2024 11:40	PM ₁₀ , PM _{2.5}	Unscheduled Maintenance	3.6	ТА	19/04/2024

This table details any missing data, data removed due to being deemed invalid, or data that has been adjusted.

Table 18: January 2024 Western Ventilation Stack data validation





6.1.5.2 January 2024 - Eastern Ventilation Stack

Eastlink Tunnel Eastern Ventilation Stack Data Validation January 2024									
Start Date	End Date	Parameters	Reason	Hours affected	User Name	Change Date			
1/01/2024 00:00	17/01/2024 05:43	со	Offset applied to data: Offset A: 0.0 Offset B: -0.3	N/A	ТА	19/04/2024			
3/01/2024 11:42	4/01/2024 06:07	Stack temp & PM ₁₀	Instrument fault	18.4	ТА	19/04/2024			
4/01/2024 06:08	4/01/2024 06:55	Stack temp & PM ₁₀	Maintenance	0.8	ТА	19/04/2024			
5/01/2024 12:36	6/01/2024 08:33	Stack temp & PM ₁₀	Instrument fault	19.9	ТА	19/04/2024			
6/01/2024 06:53	27/01/2024 06:38	All parameters	Intermittent data transmission errors	N/A	ТА	19/04/2024			
6/01/2024 08:34	6/01/2024 09:54	Stack temp & PM ₁₀	Maintenance	1.3	ТА	19/04/2024			
7/01/2024 22:21	29/01/2024 03:40	PM _{2.5} , PM ₁₀	Intermittent unrealistic data - negative	N/A	ТА	19/04/2024			
10/01/2024 09:13	10/01/2024 09:18	All parameters	Power interruption	0.1	ТА	19/04/2024			
16/01/2024 09:22	16/01/2024 17:35	Stack temp & PM ₁₀	Instrument offline	8.2	ТА	19/04/2024			
16/01/2024 17:36	16/01/2024 19:00	Stack temp & PM ₁₀	Maintenance	1.4	ТА	19/04/2024			
16/01/2024 19:52	17/01/2024 07:00	Stack temp & PM ₁₀	Instrument offline	11.1	ТА	19/04/2024			
17/01/2024 05:44	17/01/2024 06:31	Stack Temp, NO, NO ₂ , NO _x , CO, PM ₁₀ , PM _{2.5}	Scheduled monthly maintenance	0.8	ТА	19/04/2024			
17/01/2024 06:32	17/02/2024 23:30	со	Offset applied to data: Offset A: 0.0 Offset B: -0.3	N/A	ТА	19/04/2024			
17/01/2024 20:28	17/01/2024 21:53	PM _{2.5}	Unrealistic data - excessive noise	1.4	ТА	19/04/2024			
17/01/2024 22:47	18/01/2024 04:54	PM _{2.5}	Unrealistic data - excessive noise	6.1	ТА	19/04/2024			
18/01/2024 10:32	18/01/2024 13:25	Stack temp & PM ₁₀	Non-scheduled maintenance - Pump replaced	2.9	ТА	19/04/2024			
21/01/2024 11:52	22/01/2024 09:09	Stack temp & PM ₁₀	Instrument offline	21.3	ТА	19/04/2024			
22/01/2024 09:10	22/01/2024 10:00	Stack temp & PM ₁₀	Maintenance	0.8	ТА	19/04/2024			

This table details any missing data, data removed due to being deemed invalid, or data that has been adjusted. Table 19: January 2024 Eastern Ventilation Stack data validation





6.2 February 2024

6.2.1 Data Availability

Data availability for the in the ventilation stack parameters are provided in Table 20 below. For further information on data availability please refer to section 6.1.5.

EastLink Ventilation Stack Data Availability February 2024									
Station		NO	NO ₂	со	PM _{2.5}	PM ₁₀	Stack Velocity	Stack Temp.	
Western	Data Availability	87.9%	87.9%	94.5%	86.8%	98.6%	100.0%	100.0%	
	Collected Periods	612	612	658	604	686	696	696	
	Available Periods	696	696	696	696	696	696	696	
Eastern	Data Availability	95.5%	95.5%	95.5%	99.9%	97.1%	100.0%	97.1%	
	Collected Periods	665	665	665	695	676	696	676	
	Available Periods	696	696	696	696	696	696	696	

Table 20: February 2024 ventilation stack data availability





6.2.2 Exceedances

Instances of the ventilation stack pollutants exceeding the EPA Limits goals during the reporting period are presented in Table 21 below. Maximum mass rates are provided for comparison to the limits.

EastLink Ventiliation Stack Air Quality Limit Exceedances February 2024										
Location	Parameter	Time Period	Licence Limit	Units	Maximum Mass Rate	Number of exceedances	Value of exceedance	Date and Time of exceedance		
Western Ventilation Stack (Discharge Point 1)	NO ₂	1-hour	3.98	kg/h	0.60	-	-	-		
	со	1-hour	112	kg/h	6.55	-	-	-		
	PM _{2.5}	1-hour	2.4	kg/h	0.17	-	-	-		
	PM ₁₀	1-hour	2.6	kg/h	0.42	-	-	-		
Eastern Ventilation Stack (Discharge Point 2)	NO ₂	1-hour	3.98	kg/h	0.74	-	-	-		
	со	1-hour	112	kg/h	8.41	-	-	-		
	PM _{2.5}	1-hour	2.4	kg/h	0.17	-	-	-		
	PM ₁₀	1-hour	2.6	kg/h	0.83	-	-	-		

There were nil exceedances of the prescribed limits during the reporting period.

Table 21: February 2024 Exceedances of EPA Goals





6.2.3 Tabulated Results

6.2.3.1 Statistical Summary of 1-hour Mass Rate Data Western and Eastern Ventilation Stacks

Table 22 presents 1-hour mass rate statistical data for the Western and Eastern ventilation stacks.

1-hour mass rates are calculated from 1 minute average data.

EastLink Ventilation Stack Summary February 2024									
Location	Parameter	Maximum	99 th Percentile	98 th Percentile	95 th Percentile	90 th Percentile	75 th Percentile	50 th Percentile	
Western Ventilation Stack	NO (kg/h)	2.54	2.16	2.05	1.64	1.19	0.86	0.43	
	NO ₂ (kg/h)	0.60	0.41	0.28	0.22	0.17	0.12	0.08	
	CO (kg/h)	6.55	5.19	4.94	4.53	3.98	2.84	1.98	
	PM _{2.5} (kg/h)	0.2	0.1	0.1	0.1	0.1	0.1	0.0	
	PM ₁₀ (kg/h)	0.4	0.4	0.3	0.2	0.1	0.1	0.1	
Eastern Ventilation Stack	NO (kg/h)	3.25	2.86	2.64	2.24	1.90	1.36	0.57	
	NO ₂ (kg/h)	0.74	0.59	0.57	0.46	0.37	0.24	0.14	
	CO (kg/h)	8.41	6.52	6.06	5.14	3.93	2.83	2.05	
	PM _{2.5} (kg/h)	0.2	0.1	0.1	0.1	0.1	0.1	0.0	
	PM ₁₀ (kg/h)	0.8	0.4	0.4	0.3	0.2	0.1	0.1	

Table 22: February 2024 Summary of 1-hour mass rate pollutant data





6.2.4 Graphical Representations

The following charts present 1-hour mass rate data for NO, NO₂, CO, PM_{2.5}, PM₁₀ and Stack Velocity for the Western and Eastern ventilation stacks.

1-hour mass rates are calculated from 1 minute average data.

6.2.4.1 February 2024 - Monthly 1-hour mass rate NO₂




Figure 9: February 2024 Monthly 1-hour mass rate NO2





6.2.4.2 February 2024 - Monthly 1-hour mass rate NO




Figure 10: February 2024 Monthly 1-hour mass rate NO





6.2.4.3 February 2024 - Monthly 1-hour mass rate CO




Figure 11: February 2024 Monthly 1-hour mass rate CO





6.2.4.4 February 2024 - Monthly 1-hour mass rate PM_{2.5}




Figure 12: February 2024 Monthly 1-hour mass rate PM_{2.5}





6.2.4.5 February 2024 - Monthly 1-hour mass rate PM₁₀




Figure 13: February 2024 Monthly 1-hour mass rate PM₁₀





6.2.4.6 February 2024 - Monthly 1-hour average stack velocity




Figure 14: February 2024 Monthly 1-hour average stack velocity





6.2.4.7 February 2024 - Monthly 1-hour average stack temperature




Figure 15: February 2024 Monthly 1-hour average stack temperature





6.2.5 Data Validation Table

Data validation details for the ventilation stack parameters are provided in the Table 23 and Table 24 below.

6.2.5.1 February 2024 - Western Ventilation Stack

Eastlink Tunnel Western Ventilation Stack Data Validation February 2024							
Start Date	End Date	Parameters	Reason	Hours affected	User Name	Change Date	
1/02/2024 00:03	29/02/2024 23:51	PM _{2.5}	Intermittent unrealistic data - negative	N/A	ТА	22/04/2024	
7/02/2024 01:45	9/02/2024 00:59	NO, NO ₂ , NO _x	Calibration out of tolerance	47.2	ТА	22/04/2024	
10/02/2024 01:45	13/02/2024 08:17	NO	Multiplier applied to data: Multiplier A: 1.125176 Multiplier B: 1.215805	N/A	ТА	22/04/2024	
10/02/2024 01:45	13/02/2024 08:17	NO _x	Multiplier applied to data: Multiplier A: 1.137504 Multiplier B: 1.205111	N/A	ТА	22/04/2024	
20/02/2024 01:45	27/02/2024 07:47	NO	Multiplier applied to data: Multiplier A: 1.0 Multiplier B: 1.22914	N/A	ТА	22/04/2024	
20/02/2024 01:45	27/02/2024 07:47	NO _x	Multiplier applied to data: Multiplier A: 1.0 Multiplier B: 1.225136	N/A	ТА	22/04/2024	
12/02/2024 16:30	14/02/2024 00:00	PM _{2.5}	Unrealistic data - excessive noise	31.5	ТА	22/04/2024	
17/02/2024 22:44	17/02/2024 23:21	NO, NO ₂ , NO _x , CO	Scheduled Monthly Maintenance	0.6	ТА	22/04/2024	
20/02/2024 20:05	23/02/2024 04:54	PM _{2.5}	Unrealistic data - excessive noise	56.8	ТА	22/04/2024	
	27/02/2024 13:53	CO, NO, NO ₂ , NO _x	Maintenance	6.1	ТА	22/04/2024	

This table details any missing data, data removed due to being deemed invalid, or data that has been adjusted.

Table 23: February 2024 Western Ventilation Stack data validation





6.2.5.2 February 2024 - Eastern Ventilation Stack

	Eastlink Tunnel Eastern Ventilation Stack Data Validation February 2024							
Start Date	End Date	Parameters	Reason	Hours affected	User Name	Change Date		
7/02/2024 13:51	8/02/2024 08:37	Stack temp & PM ₁₀	Instrument offline	18.8	ТА	22/04/2024		
8/02/2024 08:38	8/02/2024 10:00	Stack temp & PM ₁₀	Maintenance	1.4	ТА	22/04/2024		
15/02/2024 02:05	27/02/2024 18:35	PM _{2.5} , PM ₁₀	Intermittent unrealistic data - negative	N/A	ТА	22/04/2024		
17/02/2024 23:31	18/02/2024 00:21	NO, NO ₂ , NO _x , CO, PM ₁₀ , PM _{2.5} & Stack temp	Scheduled Monthly Maintenance	0.8	TA	22/04/2024		
18/02/2024 21:52	18/02/2024 21:53	All parameters	Brief power interruption	0.0	ТА	22/04/2024		
18/02/2024 00:22	28/03/2024 12:20	со	Offset Applied to data: Offset A: 0 Offset B: -0.3	N/A	TA	22/04/2024		
24/02/2024 08:16	24/02/2024 08:17	All parameters	Brief power interruption	0.0	ТА	22/04/2024		

This table details any missing data, data removed due to being deemed invalid, or data that has been adjusted. Table 24: February 2024 Eastern Ventilation Stack data validation

WORLD RECOGNISED ACCREDITATION



6.3 March 2024

6.3.1 Data Availability

Data availability for the in the ventilation stack parameters are provided in Table 25 below. For further information on data availability please refer to section 6.2.5

	EastLink Ventilation Stack Data Availability March 2024							
Station		NO	NO ₂	со	PM _{2.5}	PM ₁₀	Stack Velocity	Stack Temp.
	Data Availability	95.0%	95.0%	95.0%	94.8%	99.2%	100.0%	100.0%
Western	Collected Periods	707.0	707.0	707.0	705.0	738.0	744.0	744.0
	Available Periods	744.0	744.0	744.0	744.0	744.0	744.0	744.0
	Data Availability	95.4%	95.4%	95.4%	99.3%	99.2%	100.0%	100.0%
Eastern	Collected Periods	710	710	710	739	738	744	744
	Available Periods	744	744	744	744	744	744	744

Table 25: March 2024 ventilation stack data availability





6.3.2 Exceedances

Instances of the ventilation stack pollutants exceeding the EPA Limits goals during the reporting period are presented in Table 26 below. Maximum mass rates are provided for comparison to the limits.

	EastLink Ventiliation Stack Air Quality Limit Exceedances March 2024									
Location	Parameter	Time Period	Licence Limit	Units	Maximum Mass Rate	Number of exceedances	Value of exceedance	Date and Time of exceedance		
Mastars	NO ₂	1-hour	3.98	kg/h	0.53	-	-	-		
Western Ventilation Stack	со	1-hour	112	kg/h	6.33	-	-	-		
(Discharge Point 1)	PM _{2.5}	1-hour	2.4	kg/h	0.23	-	-	-		
i oline i j	PM ₁₀	1-hour	2.6	kg/h	0.36	-	-	-		
Fraters	NO ₂	1-hour	3.98	kg/h	0.69	-	-	-		
Eastern Ventilation	со	1-hour	112	kg/h	8.16	-	-	-		
Stack (Discharge Point 2)	PM _{2.5}	1-hour	2.4	kg/h	0.16	-	-	_		
101112/	PM ₁₀	1-hour	2.6	kg/h	0.42	-	-	-		

There were nil exceedances of the prescribed limits during the reporting period.

Table 26: March 2024 Exceedances of EPA Goals





6.3.3 Tabulated Results

6.3.3.1 Statistical Summary of 1-hour mass rate data Western and Eastern Ventilation Stacks

Table 27 presents 1-hour mass rate statistical data for the Western and Eastern ventilation stacks.

1-hour mass rates are calculated from 1 minute average data.

EastLink Ventilation Stack Summary March 2024								
Location	Parameter	Maximum	99 th Percentile	98 th Percentile	95 th Percentile	90 th Percentile	75 th Percentile	50 th Percentile
	NO (kg/h)	2.88	2.49	2.39	1.78	1.35	0.92	0.43
	NO ₂ (kg/h)	0.53	0.35	0.33	0.26	0.21	0.13	0.08
Western Ventilation Stack	CO (kg/h)	6.33	5.30	5.17	4.50	3.87	2.83	2.01
	PM _{2.5} (kg/h)	0.2	0.1	0.1	0.1	0.1	0.0	0.0
	PM ₁₀ (kg/h)	0.4	0.2	0.2	0.2	0.1	0.1	0.0
	NO (kg/h)	3.07	2.70	2.49	2.09	1.74	1.31	0.46
	NO ₂ (kg/h)	0.69	0.57	0.50	0.42	0.32	0.22	0.12
Eastern Ventilation Stack	CO (kg/h)	8.16	6.02	5.56	4.65	3.65	2.81	2.03
	PM _{2.5} (kg/h)	0.2	0.1	0.1	0.1	0.1	0.1	0.0
	PM ₁₀ (kg/h)	0.4	0.3	0.3	0.3	0.2	0.1	0.1

Table 27: March 2024 Summary of 1-hour mass rate pollutant data





6.3.4 Graphical Representations

The following charts present 1-hour mass rate data for NO, NO₂, CO, PM_{2.5}, PM₁₀ and Stack Velocity for the Western and Eastern ventilation stacks.

1-hour mass rates are calculated from 1 minute average data.

6.3.4.1 March 2024 - Monthly 1-hour mass rate NO₂




Figure 16: March 2024 Monthly 1-hour mass rate NO2





6.3.4.2 March 2024 - Monthly 1-hour mass rate NO




Figure 17: March 2024 Monthly 1-hour mass rate NO





6.3.4.3 March 2024 - Monthly 1-hour mass rate CO




Figure 18: March 2024 Monthly 1-hour mass rate CO





6.3.4.4 March 2024 - Monthly 1-hour mass rate PM_{2.5}




Figure 19: March 2024 Monthly 1-hour mass rate PM_{2.5}





6.3.4.5 March 2024 - Monthly 1-hour mass rate PM₁₀




Figure 20: March 2024 Monthly 1-hour mass rate PM₁₀





6.3.4.6 March 2024 - Monthly 1-hour average stack velocity




Figure 21: March 2024 Monthly 1-hour average stack velocity





6.3.4.7 March 2024 - Monthly 1-hour average stack temperature




Figure 22: March 2024 Monthly 1-hour average stack temperature





6.3.5 Data Validation Table

Data validation details for the ventilation stack parameters are provided in the Table 28 and Table 29 below.

6.3.5.1 March 2024 - Western Ventilation Stack

	Eastlink Tu	innel Western Vei	ntilation Stack Data Validation N	/larch 202	24	
Start Date	End Date	Parameters	Reason	Hours affected	User Name	Change Date
1/03/2024 01:45	20/03/2024 08:49	NO	Multiplier applied to data: Multiplier A: 1.0 Multiplier B: 1.179441	N/A	ТА	22/04/2024
1/03/2024 01:45	20/03/2024 08:49	NO _x	Multiplier applied to data: Multiplier A: 1.0 Multiplier B: 1.104905	N/A	ТА	22/04/2024
1/03/2024 00:36	31/03/2024 22:54	PM _{2.5}	Intermittent unrealistic data - negative	N/A	ТА	22/04/2024
1/03/2024 00:00	10/03/2024 23:59	со	Offset Applied to data: Offset A: 0 Offset B: -0.3	N/A	ТА	22/04/2024
4/03/2024 17:11	4/03/2024 19:55	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	2.7	ТА	22/04/2024
9/03/2024 07:08	9/03/2024 23:42	PM _{2.5}	Unrealistic data - excessive noise	16.6	ТА	22/04/2024
17/03/2024 00:35	24/03/2024 23:59	со	Offset Applied to data: Offset A: -0.3 Offset B: -0.3	N/A	ТА	22/04/2024
20/03/2024 00:19	20/03/2024 02:12	PM _{2.5}	Unrealistic data - excessive noise	1.9	ТА	22/04/2024
20/03/2024 08:49	20/03/2024 09:45	CO, NO, NO ₂ , NO _x	Maintenance	0.9	ТА	22/04/2024
20/03/2024 08:49	20/03/2024 10:53	PM _{2.5}	Unrealistic data - $PM_{2.5} > PM_{10}$	2.1	ТА	22/04/2024
	28/03/2024 13:17	PM _{2.5} , PM ₁₀ , CO, NO, NO ₂ , NO _x	Scheduled 6 Monthly Maintenance	4.4	ТА	22/04/2024

This table details any missing data, data removed due to being deemed invalid, or data that has been adjusted.

Table 28: March 2024 Western Ventilation Stack data validation





6.3.5.2 March 2024 - Eastern Ventilation Stack

Eastlink Tunnel Eastern Ventilation Stack Data Validation March 2024								
Start Date	End Date	Parameters	Reason	Hours affected	User Name	Change Date		
5/03/2024 02:20	31/03/2024 03:41	PM _{2.5} , PM ₁₀	Intermittent unrealistic data - negative	N/A	ТА	22/04/2024		
7/03/2024 06:17	7/03/2024 06:18	All parameters	Brief power interruption	0.0	ТА	22/04/2024		
16/03/2024 09:21	16/03/2024 09:22	All parameters	Brief power interruption	0.0	ТА	22/04/2024		
28/03/2024 12:20	28/03/2024 14:17	CO, NO, NO ₂ , NO _x	Maintenance	1.9	ТА	22/04/2024		
28/03/2024 12:20	28/03/2024 15:58	PM _{2.5} , PM ₁₀	Maintenance	3.6	ТА	22/04/2024		

This table details any missing data, data removed due to being deemed invalid, or data that has been adjusted.

Table 29: March 2024 Eastern Ventilation Stack data validation





6.4 Data Availability Year to Date

Data availability statistics for year to date (01 January 2024 to 31 March 2024) are provided in Table 30 below:

EastLink Ventilation Stack Data Availability January 2024 to March 2024								
Station	NO	NO ₂	со	PM _{2.5}	PM ₁₀	Stack Velocity	Stack Temp.	
Western	92.8%	92.8%	95.0%	<mark>89.1%</mark>	<mark>98.9%</mark>	100.0%	100.0%	
Eastern	95.5%	<mark>9</mark> 5.5%	<mark>9</mark> 5.5%	99.2%	94.5%	100.0%	<mark>9</mark> 5.7%	

Table 30: EastLink Ventilation Stack year to date data availability






6.5 Annual Performance Statement Bubble Limits

The EPA License 2043 Condition LI_DA1 designates annual emission rate bubble limits for discharge points 1 and 2. Annual emission rates are calculated from 1st July to 30th June each year to coincide with the Annual Performance Statement (APS) reporting period. Ventilation Stack emission rates year to date (01 July 2023 to 31 March 2024) are shown in Table 31 below.

EastLink Ve	EastLink Ventilation Stack Mass Rate July 2023 to March 2024						
Location	NO ₂	СО	PM _{2.5}	PM ₁₀			
Location	Tonnes	Tonnes	Tonnes	Tonnes			
Western Ventilation Stack (Discharge Point 1)	0.373	10.482	0.171	0.321			
Eastern Ventilation Stack (Discharge Point 2)	0.834	10.868	0.216	0.466			
Total	1.208	21.350	0.387	0.788			
Percentage of Licence limit	3.5%	2.2%	1.8%	3.4%			
Annual Limit (Tonnes)	35	980	21	23			

Table 31: Annual Performance Statement stack emission rates

Figure 23 below presents the ventilation stack emissions of each parameter as a percentage of the Licence limit compared with the percentage of elapse APS Reporting period.









7 Report Summary

• There were nil exceedances of the prescribed limits during the reporting period.





Appendix 1

Glossary

The following terms and abbreviations are used in this report

CO	Carbon monoxide
DP1	Discharge Point 1
DP2	Discharge Point 2
kg/hour	Kilograms per hour
g/5m	Grams per 5 minutes
m³/s	Cubic meters per second
mg/m³	Milligrams per cubic meter at dry, standard temperature and pressure (0°C and 101.3 kPa)
NO	Nitric oxide
NO ₂	Nitrogen dioxide
PM ₁₀	Particulate less than 10 microns in equivalent aerodynamic diameter
PM _{2.5}	Particulate less than 2.5 microns in equivalent aerodynamic diameter
g/5m m ³ /s mg/m ³ NO NO ₂ PM ₁₀	Grams per 5 minutes Cubic meters per second Milligrams per cubic meter at dry, standard temperature and pressure (0°C and 101.3 kPa) Nitric oxide Nitrogen dioxide Particulate less than 10 microns in equivalent aerodynamic diameter

Data Validation Explanations

Automatic background check refers to when analyser samples zero air and measures the level of the concentration voltage. This voltage is taken as the zero signal level and this value is subtracted from any subsequent readings as an active zero compensation. This is the analyser's fine zero measurement.

Calibration check outside tolerance refers to when the calibration values are outside the tolerance limits set for the precision check.

Offset or Multiplier Applied to data refers to an offset or multiplier applied to the data. This operation may be performed for a number of reasons including: (a) when a clear trend / drift outside the tolerance limit can be demonstrated by repeated operation precision checks, (b) when a correction is required on previously logged data due to a calibration check being outside the allowable tolerance

Data transmission error refers to a period of time when the instrument could not transmit data. This may be due to a communication fault between the logger and instrument.

Equipment malfunction/instrument fault refers to a period of time when the instrument was not in the normal operating mode and did not measure a representative value of the existing conditions.

Missing data/data not available refers to a period of time when either data has been lost or could not be collected.

Instrument Alarm refers to an alarm produced by the instrument. A range of alarms can be produced depending on how operation of the instrument is being affected.

Instrument out of service refers to an unavailability of data due to an instrument being shut down for repair, maintenance, or factory calibration.





Logger error refers to when an error occurs and instrument readings are not correctly recorded by the logger.

Maintenance refers to a period of time when the logger / instrument was unavailable due to maintenance.

Overnight span/zero out of tolerance refers to when the span/zero reading measured by the analyser during an automatic precision check falls outside of the expected concentration limits.

Power Interruption refers to no power to the station therefore no data was collected at this time.

Remote Calibration refers to when a technician remotely connects to the station and manually performs a span check.

Warm up after power interruption refers to the start up period of an instrument after power has been restored.

